


Extension Cords

PowerFlex U-Ground 15A 125V NEMA 5-15 Cords



Features & Benefits

- ▶ Versatile, Water Resistant PVC Jacket rated to -31-degrees F
- ▶ No cable kinks, flaws in jacket, or cable lay issues will let the cable be used for years and years of being coiled and un-coiled
- ▶ Molded, Low Profile, tapered, snag-free ends
- ▶ Added webbed strain relief to prevent cracking and separations
- ▶ Available in a variety of colors
- ▶ Custom colors, cable surface printing or indenting is available upon request
- ▶ Triple-Tap options available*



1201

Gauge / No. of Conductors	Cat. No.	Length	Amps	Type	Color	Power Up Indicator	Box Count	Box Weight
10/3	1105	50 Ft.	15	SJTW	Yellow	No	2	24
10/3	1105R	50 Ft.	15	SJTW	Red	Yes	2	24
10/3	1101	100 Ft.	15	SJTW	Yellow	No	2	46
10/3	1101R	100 Ft.	15	SJTW	Red	Yes	2	46
12/3	1202	25 Ft.	15	SJTW	Yellow	No	6	20
12/3	1205	50 Ft.	15	SJTW	Yellow	No	6	42
12/3	1201	100 Ft.	15	SJTW	Yellow	No	4	60
12/3	1250	50 Ft.	15	STW	Yellow	No	4	42
12/3	1200	100 Ft.	15	STW	Yellow	No	2	42
12/3	1258*	50 Ft.	15	SJTW	Yellow	No	4	28
12/3	1218*	100 Ft.	15	SJTW	Yellow	No	2	26
12/3	1205BW	50 Ft.	15	SJTW	Blue/White Stripe	Yes	6	42
12/3	1205RW	50 Ft.	15	SJTW	Red/White Stripe	Yes	6	42
12/3	1205-WHITE	50 Ft.	15	SJTW	White	Yes	6	42
12/3	1205NG	50 Ft.	15	SJTW	Neon Green	Yes	6	42
12/3	1205NO	50 Ft.	15	SJTW	Neon Orange	Yes	6	42
12/3	1205NP	50 Ft.	15	SJTW	Neon Pink	Yes	6	42
12/3	1201BW	100 Ft.	15	SJTW	Blue/White Stripe	Yes	4	60
12/3	1201RW	100 Ft.	15	SJTW	Red/White Stripe	Yes	4	60
12/3	1201-WHITE	100 Ft.	15	SJTW	White	Yes	4	60
12/3	1201NG	100 Ft.	15	SJTW	Neon Green	Yes	4	60
12/3	1201NO	100 Ft.	15	SJTW	Neon Orange	Yes	4	60
12/3	1201NP	100 Ft.	15	SJTW	Neon Pink	Yes	4	60
14/3	1425	25 Ft.	13	SJTW	Orange	No	6	15
14/3	1450	50 Ft.	13	SJTW	Orange	No	6	30
14/3	1400	100 Ft.	13	SJTW	Orange	No	3	30
16/3	1625	25 Ft.	10	SJTW	Orange	No	12	25
16/3	1650	50 Ft.	10	SJTW	Orange	No	12	45
16/3	1600	100 Ft.	10	SJTW	Orange	No	6	45

Extension Cords

GlowFlex U-Ground 15A 125V NEMA 5-15 Cords



- Same features as PowerFlex
- Cords have a clear molded connector with indicator light to confirm your cord has power
- Triple-Tap*

Gauge	Cat. No.	Length	Amps	Type	Color	Receptacle Count	Box Count	Box Weight
12/3	2205	50 Ft.	15	SJTW	Yellow	1	6	44
12/3	2201	100 Ft.	15	SJTW	Yellow	1	4	54
12/3	2258*	50 Ft.	15	SJTW	Yellow	3	4	28
12/3	2218*	100 Ft.	15	SJTW	Yellow	3	2	27



2218

Extreme All Weather 15A 125V NEMA 5-15 Cords



- Construction Grade extension cord meant for the coldest and roughest environments
- Cold Weather Compound rated to -58-degrees F
- TPE Jacketing allows for soft, flexible cable that is easy to coil and uncoil
- Low Profile, tapered, snag-free ends
- Added webbed strain relief to prevent cracking and separations
- Cords have a clear molded connector with indicator light to confirm your cord has power
- Triple-Tap*



Gauge	Cat. No.	Length	Amps	Type	Color	Receptacle Count	Box Count	Box Weight
12/3	4202	25 Ft.	15	SJEOW	Blue	1	6	20
12/3	4205	50 Ft.	15	SJEOW	Blue	1	6	37
12/3	4201	100 Ft.	15	SJEOW	Blue	1	4	15
12/3	4258*	50 Ft.	15	SJEOW	Blue	3	4	26
12/3	4218*	100 Ft.	15	SJEOW	Blue	3	2	26



4201

PowerFlex Twist-Lock 20A 125V NEMA L5-20 Cords



- Versatile, Water Resistant PVC Jacket rated to -31-degrees F
- No cable kinks, flaws in jacket, or cable lay issues will let the cable be used for years and years of being coiled and un-coiled
- Low Profile, tapered, snag-free ends
- Added webbed strain relief to prevent cracking and separations
- Custom colors, cable imprinting, and labeling is available upon request

Gauge	Cat. No.	Length	Amps	Type	Color	Box Count	Box Weight
10/3	93101	100 Ft.	20	SJTW	Yellow	6	47
12/3	93185	50 Ft.	20	SJTW	Yellow	6	41
12/3	93181	100 Ft.	15	SJTW	Yellow	4	57
12/3	93155	50 Ft.	20	STW	Yellow	4	43
12/3	93151	100 Ft.	15	STW	Yellow	2	44



93181

Extension Cords

PowerFlex Extreme Twist-Lock 20A 125V NEMA L5-20 Cords



Features & Benefits


- Extra – Heavy Capacity, Construction Grade extension cord meant for the coldest and roughest environments
- Cold Weather Compound rated to -58-degrees F
- STOW Rubber-Alloy Jacketing allows for soft, flexible cable that is easy to coil and uncoil
- Low Profile, tapered, snag-free ends colored orange for visibility
- Added webbed strain relief to prevent cracking and separations



1201

Gauge	Cat. No.	Length	Amps	Type	Color	Box Count	Box Weight
12/3	92185	50 Ft.	20	SJTOW	Black	6	43
12/3	92181	100 Ft.	15	SJTOW	Black	4	54
12/3	92155	50 Ft.	20	STOW	Black	4	45
12/3	92151	100 Ft.	15	STOW	Black	2	43

PowerFlex Rubber Twist-Lock 20A 125V NEMA L5-20 Cords



Features & Benefits

- Extra – Heavy Capacity, Construction Grade extension cord meant for the coldest and roughest environments
- Cold Weather Compound rated to -58-degrees F
- Rubber Jacketing and ends make this the toughest NEMA L5-20 cable available



7395

Gauge	Cat. No.	Length	Amps	Type	Color	Box Count	Box Weight
12/3	7395	50 Ft.	20	SJOOW	Black	6	46
12/3	7391	100 Ft.	15	SJOOW	Black	4	61

REPLACEMENT PARTS AVAILABLE

Temporary Power Cable Adapters

Pigtail, 'Y' and 'W' Adapters





















1447



1480



1034

Cat. No.	Type	Length	Gauge / No. of Conductors / Type	Plug	Connector	
 	1447	Adapter	12 In.	12/3 STW	5-15P U-Ground	L5-20R Twist-Lock
 	1446	Adapter	12 In.	12/3 STW	L5-20P Twist-Lock	5-15R U-Ground
 	1473	Y Adapter	24 In.	12/3 STW	5-15P U-Ground	2 Ea. 5-15R U-Ground
 	1474	Y Adapter	24 In.	12/3 STW	L5-20P Twist-Lock	2 Ea. L5-20R Twist-Lock
	1476	Y Adapter	24 In.	12/3 STW	Blank Ends	Blank Ends
 	1479	W Adapter	24 In.	12/3 STW	5-15P U-Ground	3 Ea. 5-15R U-Ground
 	1480	W Adapter	24 In.	12/3 STW	L5-20P Twist-Lock	3 Ea. L5-20R Twist-Lock
 	1034	Y Adapter	24 In.	10/3 SOOW	L6-30P Twist-Lock	2 Ea. L6-30R Twist-Lock
 	1449	Tri-Tap Adapter	24 In.	12/3 STW	L5-20P Twist-Lock	3 Ea. 5-15R U-Ground
 	8312	Tri-Tap Adapter	24 In.	12/3 STW	5-15P U-Ground	3 Ea. 5-15R U-Ground

Cord Control System

Features & Benefits

- Keep jobsites safe and organized by suspending temporary power cords above the ground
- Cord Control systems fasten extension cords to strut or directly to a wall to reduce trip hazards
- Strut-Mounting system snaps in for easy installation
- Available in two sizes for temporary power and standard extension cords
- Non-Conductive
- Cable tie mounting port on the bottom for added security

Cat. No.	Description	Max Wire Gauge & Type
8197	Universal 2-Slot Cord Control (10-Pack)	6/4 SOOW
8198	Strut 2-Slot Cord Control (10-Pack)	6/4 SOOW
8199	Universal 4-Slot Extension Cord Control (each)	10/3 SOOW



8198

8199

REPLACEMENT PARTS AVAILABLE

Electrical Accessories

Cable Crossovers & Protection

Cat. No.	Description	Rating	Dimensions In.	Weight
3110	3 Ft. 5-Channel	40,000 Lbs. per Axle	20W x 36L x 2.31H	25 Lb.
3115	Set of Ends for PN# 3110	40,000 Lbs. per Axle	20W x 7.5 & 5.25L x 2.31H	3.5 Lb.
3111	3 Ft. 5-Channel	20,000 Lbs. per Axle	17.5W x 36L x 1.95H	18 Lb.
3116	Set of Ends for PN# 3111	20,000 Lbs. per Axle	17.5W x 4.7"L x 1.95H	2.7 Lb.



3110

Power Supply Cords

	Cat. No.	Length	Gauge	Type	Jacket	NEMA No.
	15367	8 Ft.	16/3	SJTW	Vinyl	5-15P
	15371	12 Ft.	16/3	SJTW	Vinyl	5-15P
	15228	50 Ft.	16/2	SJTW	Vinyl	1-15P
	15167	8 Ft.	16/3	SJTW	Vinyl	L5-20P
	15165	50 Ft.	16/3	SJTW	Vinyl	L5-20P
	15165S	50 Ft.	16/3	SJTOW	Rubber Alloy	L5-20P



15367

Power Blocks

	Cat. No.	Length	Plug	Connector
	8304	Block	5-15P	3 Ea. 5-15R
	8303	Block	5-15P	3 Ea. 5-15R
	1441	3 to 2 Wire	1-15P	5-15R



8304



8303

Booster Cables

Cat. No.	Length	Gauge	Type	Jacket	Color	Dimensions In.	Weight
8612	12 Ft.	6	SJTW	Vinyl	Red/Black	15W x 19L x 12H	30 Lb.
8416	16 Ft.	4	SJTW	Vinyl	Red/Black	11W x 14L x 5H	9 Lb.



8612

Professional Power Strips

- 15-Amp Breaker
- 6 Ft. 14-3 SJTW Cord
- 1050 Joules

Cat. No.	Receptacle Qty.	Material	Dimensions In.
8194	6	Plastic	8W x 15L x 13H
8195	6	HD Steel	12W x 17L x 12H
8196	12	HD Aluminium	8W x 48L x 8H



Ground Fault Circuit Interrupters (GFCI's)

Ground Fault Circuit Interrupters (GFCI's) are a safety device that are used to protect people. While mandated by OSHA and the NEC in certain locations, GFCI's are also a great idea to protect any individual. GFCI's protect people by sensing a ground fault due to a crossed wire, ground fault, or liquid fault.



















Inline and Right Angle GFCI Extension Cords













Features & Benefits

- ▶ Provides a solution for GFCI protection when needed quickly
- ▶ All inline GFCI units have rain-proof protection
- ▶ Units have test/reset buttons and indicator light.
- ▶ UL Listed for Class-A Personnel Protection, OSHA Compliant, Jobsite Tested
- ▶ All GFCI inline and right-angle devices utilize manual reset GFCI's
- ▶ GFCI meets UL 943 requirements with 4-6 milliamp trip level, <25 milliseconds trip time
- ▶ All GFCI cords with a 15 Amp plug will have a 15 Amp rated assembly
- ▶ All cords have 12 AWG 3 Conductor cord, either STW or SJTW as noted



NEMA 3R

Cat. No.		GFCI Type	Length	Jacket	Circuitry Rating	Plug	Connector	
		1440G2	Inline	2 Ft.	SJTW	15A/125V	5-15P U-Ground	3 Ea. 5-15R U-Ground
		1442G2	Inline	2 Ft.	STW	20A/125V	5-15P U-Ground	15R U-Ground
		1444G2	Inline	2 Ft.	STW	20A/125V	5-15P U-Ground	3 Ea. 5-15R U-Ground
		1445G2	Right Angle Plug	2 Ft.	SJTW	15A/125V	5-15P U-Ground	3 Ea. 5-15R U-Ground
		1242G2	Inline	2 Ft.	SJTW	20A/125V	5-15P U-Ground	15R U-Ground
		1244G2	Inline	2 Ft.	SJTW	20A/125V	5-15P U-Ground	3 Ea. 5-15R U-Ground
		1447G2	Inline	2 Ft.	STW	20A/125V	L5-20P Twist-Lock	15R U-Ground
		1446G2	Inline	2 Ft.	STW	20A/125V	5-15P U-Ground	L5-20R Twist-Lock
		1443G2	Inline	2 Ft.	STW	20A/125V	L5-20P Twist-Lock	L5-20R Twist-Lock


Cat. No.		GFCI Type	Length	Jacket	Circuitry Rating	Plug	Connector	
		1440G25	Inline	25 Ft.	SJTW	15A/125V	5-15P U-Ground	3 Ea. 5-15R U-Ground
		1440G50	Inline	50 Ft.	SJTW	15A/125V	5-15P U-Ground	3 Ea. 5-15R U-Ground
		1440G100	Inline	100 Ft.	SJTW	15A/125V	5-15P U-Ground	3 Ea. 5-15R U-Ground
		1430G25	Right Angle Plug	25 Ft.	SJTW	15A/125V	5-15P U-Ground	3 Ea. 5-15R U-Ground
		1430G50	Right Angle Plug	50 Ft.	SJTW	15A/125V	5-15P U-Ground	3 Ea. 5-15R U-Ground
		1430G100	Right Angle Plug	100 Ft.	SJTW	15A/125V	5-15P U-Ground	3 Ea. 5-15R U-Ground

Ground Fault Circuit Interrupters (GFCI's)

GFCI Plugs and Attachables

Features & Benefits

- Can be attached quickly to any power tool or used in a receptacle to add protection
- Can accept up to 12/3 Type SOOW wire
- Units have test/reset buttons
- cULus Listed, OSHA Compliant
- 15-Amp 125-Volt Rated

	Cat. No.	Device Rating	GFCI Type	Type
	1410G	15A/125V	Manual Reset	Plug
	1420G	15A/125V	Automatic Reset	Plug
	1430G	15A/125V	Manual Reset	Attachable
	1431G	15A/125V	Automatic Reset	Attachable




1410G

GFCI Multi-Outlet Boxes

Features & Benefits

- 2- or 4- outlet configurations, NEMA 5-20 or L5-20
- Units have test/reset buttons
- cULus Listed, OSHA Compliant
- Both 15-Amp and 20-Amp 125-Volt Options
- Made with 12/3 SJTW wire, 125V 15-Amp Rating

	Cat. No.	Length	Number of Outlets	Weight
	1460G6	6 Ft.	4 x NEMA 5-15R	2.25 Lb.
	1473G2	2 Ft.	4 x NEMA 5-15R	1 Lb.
	1475G2	2 Ft.	1 x NEMA L5-20R, 2 x NEMA 5-15R	3 Lb.
	1477G2	2 Ft.	2 x NEMA L5-20R	3 Lb.
	1473G2W	2 Ft.	4 x NEMA 5-15R Weatherproof Covers	3 Lb.
	1475G2W	2 Ft.	1x NEMA L5-20R, 2x NEMA 5-15R, with Weatherproof Covers	3 Lb.
	1477G2W	2 Ft.	2 x NEMA L5-20R Weatherproof Covers	3 Lb.



1477G2W



1460G6

REPLACEMENT PARTS AVAILABLE